GlobeHeat Datasheet: Product Code GHT 2474





Product Description: Chino AH4712-EOA Twelve Point Temperature Recorder

The AH4712-EOA is a hybrid analogue/digital temperature recorder with an LCD screen displaying the twelve channel's temperature values either one channel at a time, or multiple channels at the same time with the option for digital display and simultaneous bar graph display.

The recorder has the facility of printing to the paper chart and saving the data to SD card (sold separately) which can then be displayed on a PC using Report Maker software (sold separately) or the measurement data can be saved as a CSV file and displayed in an Excel worksheet. The recorder can also be connected to a network and monitored using the supplied software or from a web browser.

Applications

For recording pre and post weld heat treatment processes up to 1200°C. The recorder is housed within a resilient powder coated, mild steel* case enabling it to withstand normal site conditions in all regions of the world.

Features

- Twelve type K thermocouple sockets fitted to the rear of the unit
- Chart speeds 1 to 1500mm /hour in 1mm Increments
- Chart and scale illumination allowing the operator to view the chart detail in low light conditions
- One EH05035 (0-1200°C) chart paper supplied as standard
- SD Card (supplied separately GHT 2514) to export data to PC via report maker software (supplied separately GHT 2482)
- Ethernet connection for Web Viewer and E-mail Alarm notifications (via supplied software KIDS)
- 4 Alarm Types (no relay output)
- Ergonomic folding handle fitted to each side of the case

Specification	
Supply Voltage	110V AC @ 50/60 Hz (230V AC available on request)
Thermocouple Input	Type K (NiCr/NiAl), Twelve Channels
Recording System	Wire-dot type six-colour ribbon: Dotting Interval 5 or 2.5 seconds/point
Temperature Recording Range	0 to 1200° C
Digital display	Full dot monochrome LCD 264 x 48 dots Display area 184 x 22mm
Measurement Accuracy	±0.1%FS ±1digit
Illumination	White LED backlight (turned off after 3-minute unused period when selecting AUTO)
Operating Temperature	0 to 50° C (20 to 65%RH, non-condensing)
Replacement chart paper pack	EH05035 (0-1200°C) Chino chart
Case Material	Standard unit is powder coated, mild steel (*stainless steel case available on request)
Dimensions	430mm x 355mm x 365mm
Weight	18 kg
Design Standards	EMC: EN 61326-1, LVD: EN 61010-1





GlobeHeat Datasheet: Product Code GHT 2474









Additional accessories and spares



SD Card Industrial Grade 2GB Product Code: GHT2514



Report Maker (RM11) Software Product Code: GHT2482



Chino Cassette Ribbon Product Code: GHT2406



Chino Linear Chart EH05035 0-1200°C Product Code: GHT2406



